

CLEARVUE™

VIDEO LARYNGOSCOPE



CLEARVUE™

The Infinium ClearVue™ VL3D

Disposable Blade Video Laryngoscopes

The **Infinium ClearVue™** video laryngoscope adopts state-of-the-art image technology and possesses the advantage of a 2.0 megapixel full view camera with 4 inch high-resolution monitor. The **ClearVue™** features a rechargeable li-ion battery for extended use. The HD screen offers a unique anti-fog and anti-shatter capability. The overall design is compact and ergonomic. A high-resolution view of the glottis will enable clinicians first-attempt success while minimizing any chance of a complication during the intubation process.

The Infinium ClearVue™ Video Laryngoscopes are:

COMPACT AND INNOVATIVE

- Lightweight - Unit Is Less Than 350g
- Rigid Steel Construction
- Quick installation and Removal of Blades
- Quick Shot Camera Button for Photo and Video Recording
- 4 GB Data Storage (Approx. 80 Minutes of Stored Video)
- Optional HDMI Output for Remote Display

COMPREHENSIVE BLADE OFFERING

- Macintosh Blades Size 1,2,3,4,5 Available
- Macintosh Channeled Blades Size 1,2,3,4,5 Available



DURABLE

- 1 Years Warranty
- Screen Reinforced with Anti-Shatter Protection
- Light Weight Long Lasting Rechargeable Li-ion Battery

HIGH-DEFINITION

- 4 Inch HD Display
- Anti-Fog Lens
- 2.0 Mega Pixel Camera With Video



Size 1, 2, 3, 4, and 5 disposable Mac blades are available for the ClearVue™ VL3D.

CLEARVUE™ TECHNICAL SPECIFICATIONS:

DISPLAY

Size	4" Full View
Monitor	LCD; Scratch-resistant and anti-glare screen
Resolution Ratio	640*480 RGB
Aspect Ratio	4:3
Video Refresh Rate	30FPS
Illumination	LED

LARYNGOSCOPE BLADE CAMERA INCLUDED

Resolution Ratio	2.0M Pixels
Field Angle	66°
Illuminance	≥800LUX

BATTERY

Type	Rechargeable Lithium Battery
------	------------------------------

Long working time	≥120minutes
Voltage	3.7V
Capacity	3200mAh
Charging times	More than 300 times
Charging time	4 hours

POWER ADAPTER

Charging port	Micro USB
Input	100-250V,50/60Hz
Output	5V/ 2A

TRANSPORT/ STORAGE

Temperature	-10 ~+45
-------------	----------

CONDITION

Humidity	≤93
AP	500hPa to 1060hPa

WORKING CONDITION

Temperature	5 ~+40
Humidity	30 ~85
AP	700hPa to 1060hpa

UNIQUE ANTI-FOG FUNCTION

Auto anti-fog function upon powering on

WEIGHT

321 g(disposable system); 376g (reusable system)
- light-weight, portable, comfortable

PHOTO/VIDEO FUNCTION

One click image capture 4G internal memory card for video and images USB connection cable for uploading images and video

HANDLE

ABS material - Comfortable ergonomic short handle design

CLEARVUE ORDER INFORMATION & PART NUMBERS

00.300.0008	Laryngoscope 4in display kit with a set of disposable blades	306.300.0013	Laryngoscope Disposable Channeled Blade No.1
306.300.0008	Laryngoscope disposable blade No.1	306.300.0014	Laryngoscope Disposable Channeled Blade No.2
306.300.0009	Laryngoscope disposable blade No.2	306.300.0015	Laryngoscope Disposable Channeled Blade No.3
306.300.0010	Laryngoscope disposable blade No.3	306.300.0016	Laryngoscope Disposable Channeled Blade No.4
306.300.0011	Laryngoscope disposable blade No.4	306.300.0017	Laryngoscope Disposable Channeled Blade No.5
306.300.0012	Laryngoscope disposable blade No.5		